

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1. (original) Output device for a container (6) which comprises a bottom and a surrounding wall, comprising a hub (1) and at least two arms (3) fixed to the hub (1), characterized in that each arm is designed with
 - at least one outer section designed and arranged to at use being capable of essentially preventing material from being brought towards the wall of the container, and
 - at least one inner section connected to the outer section, designed and arranged to at use being capable of bringing the material essentially in the direction of feed for the device, at whichthe at least two arms present essentially concave surfaces facing the direction of feed.
2. (original) Output device according to claim 1, characterized in that each arm (3) is continuously bent.
3. (currently amended) Output device according to ~~any of the preceding claims~~ claim 1, characterized in that the arms (3) extend essentially to the wall of the container (6).
4. (currently amended) Output device according to ~~any of the preceding claims~~ claim 1, characterized in that the arms (3) are designed with a wedge-shaped cross section, where the wedge-shape tapers contrary to the direction of feed.

5. (currently amended) Output device according to ~~any of the preceding claims~~ claim 1, characterized in that a frame (2) is arranged adjacent to the outer ends of the arms (3).

6. (original) Output device according to claim 5, characterized in that the frame (2) is fixed to the arms (3).

7. (original) Output device according to claim 5, characterized in that the frame (2) is fixed to the container (6).

8. (currently amended) Output device according to ~~any of the preceding claims~~ claim 1, characterized in a driving device capable of driving the device with a rotating movement.

9. (currently amended) Output device according to ~~any of claims 1-3~~ claim 1, characterized in a driving device capable of driving the device with a reciprocating movement.

10. (currently amended) Output device according to ~~any of the preceding claims~~ claim 1, characterized in that it is intended to be used in a container (6) with at least one principally gap-shaped discharge opening (5) located between the hub and the outer ends of the arms (3).